

Casing - Metric Guide

OD In.	OD mm	Nominal Weight		Wall thickness		Tubular Coupling OD		Drift Meter	
		lb/ft	kg/m	in.	mm	in.	mm	in.	mm
4 1/2	114.3	9.5	14.14	.205	5.21	5.000	127.0	3.965	100.71
4 1/2	114.3	10.5	15.63	.224	5.69	5.000	127.0	3.927	99.74
4 1/2	114.3	11.6	17.26	.250	6.35	5.000	127.0	3.875	98.42
4 1/2	114.3	13.5	20.09	.290	7.37	5.000	127.0	3.795	96.39
4 1/2	114.3	15.1	22.47	.337	8.56	5.000	127.0	3.701	94.00
5	127.0	11.5	17.11	.220	5.59	5.563	141.3	4.435	112.65
5	127.0	13.0	19.35	.253	6.43	5.563	141.3	4.369	110.97
5	127.0	15.0	22.32	.296	7.52	5.563	141.3	4.283	108.78
5	127.0	18.0	26.79	.362	9.19	5.563	141.3	4.151	105.43
5 1/2	139.7	14.0	20.83	.244	6.20	6.050	153.7	4.887	124.12
5 1/2	139.7	15.5	23.07	.275	6.98	6.050	153.7	4.825	122.55
5 1/2	139.7	17.0	25.30	.304	7.72	6.050	153.7	4.767	121.08
5 1/2	139.7	20.0	29.76	.361	9.17	6.050	153.7	4.653	118.18
5 1/2	139.7	23.0	34.23	.415	10.54	6.050	153.7	4.545	115.44
6 5/8	168.3	20.0	29.76	.288	7.32	7.390	187.7	5.924	159.46
6 5/8	168.3	24.0	35.72	.352	8.94	7.390	187.7	5.796	147.21
6 5/8	168.3	28.0	41.67	.417	10.59	7.390	187.7	5.666	143.91
6 5/8	168.3	32.0	47.62	.475	12.06	7.390	187.7	5.555	140.97
7	177.8	17.0	25.30	.231	5.87	7.656	194.5	6.413	162.89
7	177.8	20.0	29.76	.272	6.91	7.656	194.5	6.331	160.80
7	177.8	23.0	34.23	.317	8.05	7.656	194.5	6.241	158.52
7	177.8	26.0	38.69	.362	9.19	7.656	194.5	6.151	156.23
7	177.8	29.0	43.16	.408	10.36	7.656	194.5	6.059	153.89
7	177.8	32.0	47.62	.453	11.51	7.656	194.5	5.969	151.61
7	177.8	35.0	52.09	.498	12.65	7.656	194.5	5.879	149.32
7	177.8	38.0	56.55	.540	13.72	7.656	194.5	5.795	147.19
7 5/8	193.7	24.0	35.72	.300	7.62	8.500	215.9	6.900	175.26
7 5/8	193.7	26.4	39.29	.328	8.33	8.500	215.9	6.844	173.83
7 5/8	193.7	29.7	44.20	.375	9.52	8.500	215.9	6.750	171.45
7 5/8	193.7	33.7	50.15	.430	10.92	8.500	215.9	6.640	168.65
7 5/8	193.7	39.0	58.04	.500	12.70	8.500	215.9	6.500	165.10
8 5/8	219.1	24.0	35.72	.264	6.71	9.625	244.5	7.972	202.48
8 5/8	219.1	28.0	41.67	.304	7.72	9.625	244.5	7.892	200.45
8 5/8	219.1	32.0	47.62	.352	8.94	9.625	244.5	7.796	198.01
8 5/8	219.1	36.0	53.57	.400	10.16	9.625	244.5	7.700	195.28
8 5/8	219.1	40.0	59.53	.450	11.43	9.625	244.5	7.600	193.04
8 5/8	219.1	44.0	65.48	.500	12.70	9.625	244.5	7.500	190.50
8 5/8	219.1	49.0	72.92	.557	14.15	9.625	244.5	7.386	187.60
9 5/8	244.5	32.3	48.07	.312	7.92	10.625	269.9	8.845	224.66
9 5/8	244.5	36.0	53.57	.352	8.94	10.625	269.9	8.765	222.62
9 5/8	244.5	40.0	59.53	.395	10.03	10.625	269.9	8.679	220.44
9 5/8	244.5	43.5	64.74	.435	11.05	10.625	269.9	8.599	218.41
9 5/8	244.5	47.0	69.94	.472	11.99	10.625	269.9	8.525	216.53
9 5/8	244.5	53.5	79.62	.545	13.84	10.625	269.9	8.379	212.82
10 3/4	273.0	32.7	48.74	.279	7.09	11.750	298.5	10.036	254.91
10 3/4	273.0	40.5	60.27	.350	8.89	11.750	298.5	9.894	251.30
10 3/4	273.0	45.5	67.71	.400	10.16	11.750	298.5	9.794	248.76
10 3/4	273.0	51.0	75.90	.450	11.43	11.750	298.5	9.694	246.21
10 3/4	273.0	55.5	82.59	.495	12.57	11.750	298.5	9.604	243.93
10 3/4	273.0	60.7	90.33	.545	13.84	11.750	298.5	9.504	241.40
10 3/4	273.0	65.7	97.77	.595	15.11	11.750	298.5	9.404	238.86
11 3/4	298.4	42.0	62.50	.333	8.46	12.750	323.9	10.928	277.56
11 3/4	298.4	47.0	69.94	.375	9.52	12.750	323.9	10.844	275.43
11 3/4	298.4	54.0	80.36	.435	11.05	12.750	323.9	10.724	272.38
11 3/4	298.4	60.0	89.29	.489	12.42	12.750	323.9	10.616	269.64
13 3/8	339.7	48.0	71.43	.330	8.38	14.375	365.1	12.559	318.99
13 3/8	339.7	54.5	81.10	.380	9.65	14.375	365.1	12.459	316.45
13 3/8	339.7	61.0	90.78	.430	10.92	14.375	365.1	12.359	313.91
13 3/8	339.7	68.0	101.19	.480	12.19	14.375	365.1	12.259	311.37
13 3/8	339.7	72.0	107.15	.514	13.06	14.375	365.1	12.191	309.64
16	406.4	65.0	96.73	.375	9.52	17.000	431.8	15.062	382.57
16	406.4	75.0	111.60	.438	11.13	17.000	431.8	14.938	379.43
16	406.4	84.0	125.00	.495	12.57	17.000	431.8	14.822	376.48
18 5/8	473.0	87.5	130.21	.435	11.05	20.000	501.7	17.567	446.20
20	508.0	94.0	139.89	.438	11.13	21.000	533.4	18.936	480.97
20	508.0	106.5	158.49	.500	12.70	21.000	533.4		
20	508.0	133.0	197.92	.635	16.13	21.000	533.4		